

Specifications	VR	VR30	VR32	VR40	VR50	VR60	VR70	VR80	VR90
Table									
Table Magnetic Chuck Size		29.53" / 750mm	31.5" (800mm)	39.37" (1000mm)	49.21" (1250mm)	62.99" (1600mm)	70.86"	78.74"	88.58"
Rotary Speed		16RPM / 24RPM	5~22 rpm	6rpm/12rpm/24rpm	16rpm/24rpm	5~18rpm			
Table Movement		17.71" / 450mm	17.71"(450mm)	20.86"(530mm)	22.83"(580mm)	22.83"(580mm)			
Main Dimensions									
Max. Workpiece Height		11.81" / 300mm	12.6" (320mm)	11.81" (300mm)	15.74" (400mm)	15.74" (400mm)	40.00"	63"	63"
Max. Workpiece Weight		1323lbs / 600kg	1,323lbs (600kg)	1,764lbs (800kg)	2,867lbs (1300kg)	3,529lbs (1600kg)	4,200 lbs	5,300lbs	6,800lbs
Wheelhead									
Wheel Size		17.71" / 450mm	17.71" (450mm)	150X80X25mm	150X80X25mm	150X35X90mm			
Motor Power		33.5hp / 25 kw	40.2 hp (30 kw)	40hp (30 kw)	72hp (55 kw)	98hp (75 kw)	100 hp	100hp	100hp
Wheel Max. Speed		1200RPM	1,000rpm	750rpm	750rpm	590rpm			
Min. Increment On Downfeed Handwheel		0.0005" / 0.0127mm	0.0005" (0.0127mm)	0.0005" (0.0127 mm)	0.0005" (0.0127mm)	0.0005" (0.0127mm)			
Max. Auto Downfeed Amount		0.086" / 2.2mm	0.086" (2.2mm)	0.002~0.047inch/min (0.08~1.2mm/min)	0.002~0.047inch/min (0.08~1.2mm/min)	0.004~0.078inch/min (0.1~2mm/min)			